

# Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 22-Jan-2015

# **1. PRODUCT AND COMPANY IDENTIFICATION**

Product Identifier Product Name: Product Number: Recommended Use: Uses Advised Against:	<b>CARPET STAIN REMOVER</b> 6374 Cleaning agent For Industrial and Institutional Use Only
Manufacturer/Supplier:	Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com
24 Hour Emergency Phone Number Medical Emergency/Information Transportation/Spill/Leak:	
2. HAZARDS IDENTIFICATIO	N
<b>GHS Classification</b> Serious Eye Damage/Eye Irritation: Flammable Aerosols Gases Under Pressure	Category 2A Category 1 Liquefied gas
<u>GHS Label Elements</u> Signal Word: Symbols:	Danger
Hazard Statements:	Causes serious eye irritation Extremely flammable aerosol. Contains gas under pressure; may explode if heated
Precautionary Statements: Prevention:	Wash hands and any exposed skin thoroughly after handling. Wear eye / face protection Keep away from heat/sparks/open flames/hot surfaces. — No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Response: -Eyes -Specific Treatment:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Storage: Disposal:	Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C) Store in a well-ventilated place Not Applicable

#### Hazards Not Otherwise Classified: Not Applicable

## **Other Information:**

#### Not Applicable

- May cause skin irritation.
  - May be harmful if swallowed.
  - Inhalation of vapors or mist may cause respiratory irritation.
  - Keep out of reach of children.

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%
water	7732-18-5	60-100
2-butoxyethanol	111-76-2	5-10
isopropanol	67-63-0	1-5
propane	74-98-6	1-5
N-butane	106-97-8	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES		
-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.	
-Skin Contact:	Wash with soap and water. If skin irritation occurs: Get medical attention.	
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell.	
-Ingestion:	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell.	
Note to Physicians:	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		
Suitable Extinguishing Media: Specific Hazards Arising from the Chemical: Hazardous Combustion Products:	Water spray (fog), Foam Extremely flammable aerosol. Exposure to high temperature may cause containers to burst. Bursting aerosol containers may be propelled from fire at high speed. May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.	
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Water may be used to cool closed containers to prevent pressure build-up	

## 6. ACCIDENTAL RELEASE MEASURES

and possible auto ignition or explosion when exposed to extreme heat.

Personal Precautions:Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.Environmental Precautions:Do not rinse spill onto the ground, into storm sewers or bodies of water.Methods for Clean-Up:Prevent further leakage or spillage if safe to do so. Contain and collect spillage with<br/>non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite)<br/>and place in container for disposal according to local / national regulations (see Section 13).

# 7. HANDLING AND STORAGE

Advice on Safe Handling:

Handle in accordance with good industrial hygiene and safety practice. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash thoroughly after handling.

#### Storage Conditions:

NFPA 30B Level 1 Aerosol. Do not store in direct sunlight or above  $122 F^{\circ} / 50 C^{\circ}$ . Exposure to high temperature may cause containers to burst. Keep out of the reach of children.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
2-butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>
isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
N-butane 106-97-8	TWA: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>

**Engineering Controls:** 

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

Personal Protective Equipment	
Eye/Face Protection:	Wear splash goggles.
Skin and Body Protection:	Not required with expected use.
Respiratory Protection:	Not required with expected use.
	If occupational exposure limits are exceeded or respiratory irritation occurs, use of a
	NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section
	3 should be considered.
General Hygiene Considerations:	Wash hands and any exposed skin thoroughly after handling.
	See 29 CFR 1910.132-138 for further guidance.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Aerosol
Color:	White
Odor:	solvent
pH:	10.0-11.0
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	100 °C / 212 °F (Product without propellant)
Flash Point:	< -18 °C / < 0 °F (Propellant-estimated)
Evaporation Rate:	<1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	0.96 (Product without propellant)
Solubility(ies):	No information available.
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

# **10. STABILITY AND REACTIVITY**

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions:	Not expected to occur with normal handling and storage.
Conditions to Avoid:	Extremes of temperature and direct sunlight.
Incompatible Materials:	Strong oxidizing agents. Strong acids.
Hazardous Decomposition	May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.
Products:	

# 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Symptoms of Exposure:	Eyes, Skin, Ingestion, Inhalation.
-Eve Contact:	Pain, redness, swelling of the conjunctiva and blurred vision.
-Skin Contact:	Drying of the skin.
-Inhalation:	Nasal discomfort and coughing.
-Ingestion:	Pain, nausea, vomiting and diarrhea.
Immediate, Delayed, Chronic Effect	ts
Product Information:	Data not available or insufficient for classification.
Target Organ Effects:	-Eyes. Respiratory SystemSkin. Blood. Central nervous system. hematopoietic system. kidney. Liver,
Numerical Measures of Toxicity	

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral):	4331 mg/kg
ATEmix (dermal):	11323 mg/kg
ATEmix (inhalation-gas):	10511385
ATEmix (inhalation-dust/mist):	23.1 mg/l
ATEmix (inhalation-vapor):	22.9 mg/l

# Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water	> 90 mL/kg (Rat)	Not Available	Not Available
7732-18-5			

#### 6374 - CARPET STAIN REMOVER

2-butoxyethanol	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (	= 2.21 mg/L (Rat) 4 h = 450 ppm
111-76-2		Rabbit )	( Rat ) 4 h
isopropanol	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rat) = 12870	= 72.6 mg/L (Rat)4 h
67-63-0		mg/kg (Rabbit)	
propane	Not Available	Not Available	= 658 mg/L (Rat)4 h
74-98-6			
N-butane	Not Available	Not Available	= 658 mg/L (Rat)4 h
106-97-8			

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

# **12. ECOLOGICAL INFORMATION**

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
2-butoxyethanol 111-76-2	Not Available	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	Not Available	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
isopropanol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	Not Available	13299: 48 h Daphnia magna mg/L EC50

Persistence and Degradability:	No information available.
Bioaccumulation:	No information available.

Other Adverse Effects:

No information available.

## **13. DISPOSAL CONSIDERATIONS**

Disposal of Wastes:Dispose of in accordance with federal, state and local regulations.Contaminated Packaging:Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with federal, state and local regulations.

# **14. TRANSPORT INFORMATION**

DOT:	
UN/ID No:	UN1950
Proper Shipping Name:	Aerosols
Hazard Class:	2.1
Special Provisions:	This product meets the exception requirements of section 49 CFR 173.306 as a limited quantity and may be shipped as a limited quantity.

#### **15. REGULATORY INFORMATION**

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory) All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### SARA 313

This product contains the following listed substances:

## 2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230

# SARA 311/312 Hazard Categories

Acute Health Hazard:

Yes

Chronic Health Hazard:	No
Fire Hazard:	No
Sudden release of pressure hazard:	Yes
Reactive Hazard:	No

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
formaldehyde - 50-00-0	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

# **16. OTHER INFORMATION**

NFPA	Health Hazards: 2	Flammability: 1	Instability: 0	Special: N/A
HMIS	Health Hazards: 2	Flammability: 2	Physical Hazards: 2	

**Revision Date: Reasons for Revision:** 

22-Jan-2015 No information available.

#### **Disclaimer:**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**